

SAFETY DATA SHEET

Autoclaved Aerated Concrete (AAC)

SECTION 1. PRODUCT IDENTIFICATION

PRODUCT NAMES:	MAXIWALL / MAXIFLOOR Autoclaved Aerated Concrete (AAC) Building Panels
PRODUCT USE:	As load bearing and non-load bearing component for interior and exterior walls and floors.
SUPPLIER:	Big River Group Trenayr Road Junction Hill NSW 2460 Ph 1300 88 1958 www.bigrivergroup.com.au

SECTION 2. HAZARD IDENTIFICATION

HAZARDOUS NATURE:	Maxiwall / Maxifloor AAC as supplied is non-Hazardous. Dust from this product is classified as Hazardous according to the Approved Criteria for Classifying Hazardous Substances [NOHSC:1008] 3rd Edition. When concrete products are cut, sawn, abraded or crushed, dust is created which contains crystalline silica, some of which may be respirable (particles small enough to go into the deep parts of the lung when breathed in), and which is Hazardous.
--------------------------	--

The following GHS classifications refer ONLY to the dust of these products:

<p>GHS Classification:</p> <ul style="list-style-type: none"> Skin Irritation Category 2 Eye Irritation Category 2A Specific Target Organ Toxicity (Single Exposure) Category 3 Specific Target Organ Toxicity (Repeated Exposure) Category 2 	<p>GHS Pictograms: </p> <p>GHS Signal Word: WARNING</p>
---	--

The following GHS Hazard and Precautionary statements refer only to the dust produced by Maxiwall AAC:

<p>GHS Hazard Statements:</p> <ul style="list-style-type: none"> H315 – Causes skin irritation H319 – Causes serious eye irritation H335 – May cause respiratory irritation H373 – May cause damage to organs through prolonged or repeated exposure by inhalation 	<p>GHS Precautionary Statements:</p> <p>P260 – Do not breathe dust.</p> <p>P264 – Wash thoroughly after handling.</p> <p>P271 – Use only outdoors or in a well-ventilated area.</p> <p>P280 – Wear eye/face protection and protective gloves.</p> <p>P302 + P352 – If on skin, wash with plenty of soap and water.</p> <p>P304 + P340 – If inhaled, remove victim to fresh air and keep at rest in a position comfortable for breathing.</p> <p>P305 + P351 + P338 – If in eyes, rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.</p> <p>P312 – Call a Poison Centre or doctor if you feel unwell.</p> <p>P332 + P313 – If skin irritation occurs, get medical advice/attention.</p> <p>P337 + P313 – If eye irritation persists, get medical advice/attention.</p> <p>P362 – Take off contaminated clothing and wash before reuse.</p> <p>P403 + P233 – Store in a well-ventilated place and keep container tightly closed.</p>
--	--

AAC is classified as Non-Dangerous Goods according to the Australian Code for the Transport of Dangerous Goods by Road and Rail.



SAFETY DATA SHEET

Autoclaved Aerated Concrete (AAC)

SECTION 3. INGREDIENTS COMPOSITION & INFORMATION

Component:	Synonyms:	Proportion:	CAS Number:
Calcium Silicate Hydrate	Tobermorite	<60-80%	1344-95-2
Crystalline Silica	Quartz	20-40%	14808-60-7
Portland Cement	Concrete	10-60%	65997-15-1
Additives	Glenium, Superplasticiser	<5%	

Note: Cement in concrete contains traces (2-20 ppm) of Chromium VI (hexavalent)

SECTION 4. FIRST AID MEASURES

INHALATION:	Provide fresh air. If persistent irritation, severe coughing, or breathing difficulty occurs, seek medical attention.
EYE CONTACT:	Flush eyes, including under eyelids, with clean flowing water for 15 minutes. If irritation persists, seek medical attention.
SKIN CONTACT:	Remove any contaminated clothing. Wash skin thoroughly with soap and water. Shower if necessary. Seek medical attention for persistent redness, irritation or burning of the skin.
INGESTION:	Rinse mouth and lips with water. Do not induce vomiting. If symptoms persist, seek medical attention.

SECTION 5. FIRE FIGHTING MEASURES

SUITABLE EXTINGUISHING MEDIA:	Use carbon dioxide, foam, dry chemical or water spray as required for fire in surrounding materials.
SPECIFIC HAZARDS:	None
SPECIAL PROTECTIVE EQUIPMENT AND PRECAUTIONS FOR FIREFIGHTERS:	As required for fire in surrounding materials.
HAZCHEM CODE:	None allocated

SECTION 6. ACCIDENTAL RELEASE MEASURES

PERSONAL PRECAUTIONS, PPE AND EMERGENCY PROCEDURES:	Avoid generating dust. Recommendations on Exposure Controls / PPE (see Section 11 below) should be followed during spill clean-up if conditions are dusty.
ENVIRONMENTAL PRECAUTIONS:	None required.
METHODS AND MATERIALS FOR CONTAINMENT AND CLEAN UP:	Collect and reuse where possible. Dust is best cleaned up by vacuum device to avoid making dust airborne. Wetting down before sweeping up dust is recommended.

SECTION 7. HANDLING AND STORAGE

PRECAUTIONS FOR SAFE HANDLING:	AAC is a heavy material, and appropriate control of manual handling risk is required. Manual handling should be in accordance with Manual Handling Regulations and Codes.
CONDITIONS FOR SAFE STORAGE	No special requirements. Safety aspects of stockpiles and storage areas require risk assessment and control.
INCOMPATIBILITIES:	None

SAFETY DATA SHEET

Autoclaved Aerated Concrete (AAC)

SECTION 8. EXPOSURE CONTROLS / PERSONAL PROTECTIVE EQUIPMENT

RESPIRATORY PROTECTION:	<p>The type of respiratory protection required depends on the concentration of the respirable crystalline silica dust in the air, and the frequency and length of exposure time. A suitable P1 or P2 particulate respirator used in accordance with AS 1715 and 1716 may be sufficient for many situations, but where high levels of dust are encountered, more efficient cartridge-type or powered respirators or supplied-air helmets or suits may be necessary. Use only respirators that bear the Australian Standards mark and are fitted and maintained correctly.</p> <p>None required if engineering and handling controls are adequate to minimize dust generation and dust exposure. Where engineering and handling controls are not enough to minimise exposure to dust, personal respiratory protection may be required.</p>
EYE PROTECTION:	Use of protective safety glasses or goggles is recommended for dust generating operations.
SKIN PROTECTION:	It is recommended to wear loose comfortable clothing and gloves

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Boiling Point:	N/A	Specific gravity:	0.4 - 0.7
Vapour pressure:	N/A	Evaporation rate:	N/A
Vapour density (Air=1):	N/A	Melting point:	N/A
Solubility in water (%weight):	N/A	Volatiles (by volume):	N/A
pH:	8.0---10.0	VOC's (g/litre)	N/A
Appearance and odour: Off white with no odour			
Flash point:	N/A		
Flammability (LEL, HEL):	N/A		
Hazardous combustion products:	None		
Unusual fire and explosion hazards:	None		
Special firefighting procedures:	Applicable for surrounding materials and substances		

SECTION 10. STABILITY AND REACTIVITY

Stability:	Stable
Conditions to avoid:	None
Incompatible materials:	None as this is an inert material
Hazardous decomposition products:	None
Hazardous polymerisation:	Will not occur

SECTION 11. TOXICOLOGICAL INFORMATION

SWALLOWED:	Unlikely under normal industrial use, but swallowing the dust from this product may result in abdominal discomfort.
EYES:	<p>Short-term: Dust is irritating to the eyes causing watering and redness. Exposure to dust may aggravate pre-existing eye conditions.</p> <p>Long-term: Dust may cause irritation and inflammation of the eyes and aggravate pre-existing eye conditions.</p>
SKIN:	Short-term: The dust from this product, particularly in association with heat and

SAFETY DATA SHEET

Autoclaved Aerated Concrete (AAC)

	<p>sweat, may cause irritation. The dust is not absorbed through the skin but, may be mildly irritating and drying to the skin due to its physical characteristics.</p> <p>Long-term: Repeated heavy contact with the dust may cause drying of the skin and can result in skin rash typically affecting the hands. Over time this may become chronic and can also become infected.</p>
INHALED:	<p>Short-Term: Dust is mildly irritating to the nose, throat and respiratory tract and may cause coughing and sneezing. Pre-existing upper respiratory and lung diseases including asthma and bronchitis may be aggravated.</p> <p>Long-Term: Repeated exposure to the dust may result in increased nasal and respiratory secretions and coughing. Inflammation of lining tissue of the respiratory system may follow repeated exposure to high levels of dust with increased risk of bronchitis and pneumonia.</p>

SECTION 12. ECOLOGICAL INFORMATION

ECO-TOXICITY:	Products as delivered are not biodegradable, have low ecotoxicity and are not regarded as posing any ecological risk. Crushed product and dust may form a mildly alkaline or neutral slurry when mixed with water.
PERSISTENCE & DEGRADABILITY:	Product is persistent and would have a low degradability.
BIOACCUMULATIVE POTENTIAL:	There is no evidence to suggest bioaccumulation will occur.
MOBILITY IN SOIL:	A low mobility would be expected in a landfill situation.

SECTION 13. DISPOSAL

WASTE DISPOSAL:	AAC can be treated as a common waste for disposal or dumped into a landfill site in accordance with local, state or federal authority guidelines. Crushed product and dust should be kept out of storm water and sewer drains. Measures should be taken to prevent dust generation during disposal, and exposure and personal precautions should be observed.
------------------------	---

SECTION 14. TRANSPORT INFORMATION

UN number:	None allocated
UN Proper Shipping Name:	None allocated
Class and Subsidiary Risk :	None allocated
Packaging Group:	None allocated
Special Precautions for User:	None
HAZCHEM code:	None allocated

SECTION 15. REGULATORY INFORMATION

POISONS:	None Scheduled
Exposures by inhalation to high levels of dust may be regulated under the Hazardous Substances Regulations (State) as they are applicable to Respirable Crystalline Silica, requiring exposure assessment, controls and health surveillance.	

SECTION 16. OTHER INFORMATION

FURTHER INFORMATION CONTACT:	<p>Big River Group Big River Group Trenayr Road Junction Hill NSW 2460</p> <p>Ph 1300 88 1958 www.bigrivergroup.com.au</p>
-------------------------------------	--



SAFETY DATA SHEET

Autoclaved Aerated Concrete (AAC)

DISCLAIMER

The information contained in this material Safety Data Sheet is believed to be reliable. No guarantee is implied or expressed regarding the accuracy of this information or the use of the product since the conditions of use are beyond manufacturer's control. Nothing contained herein should be construed as a recommendation to use this product in conflict with existing patents covering any material or its use.

This SDS was generated from information available of the components of this product.
SDS date of preparation: 29th January 2021